

GENSET MODEL

Model	P 252
Mechanical version	Open version with compact base frame and high capacity integrated fuel tank without collection basin.
Fuel Tank Capacity l.	520

RATED TECHNICAL DATA

Prime Power (PRP)	225.00 kVA
Prime Power (PRP)	180.00 kW
Limited Power (LTP)	250.00 kVA
Limited Power (LTP)	200.00 kW
Rated Power Factor (cosφ)	0.8
Windings	Three phases Parallel Star
Rated three-phase concatenated voltage	208 V
Rated phase-neutral voltage	120 V
Rated frequency	60 Hz
Fuel type	Diesel

DIMENSIONS AND NOISE


Length	2430 mm
Width	1120 mm
Height	2000 mm
Weight	1850 kg
Sound pressure 7 m.	- dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	61.10 l/h
Fuel Cons. at 100% (P.R.P.)	54.50 l/h
Fuel Cons. at 75% (P.R.P.)	40.40 l/h
Fuel Cons. at 50% (P.R.P.)	27.80 l/h
Fuel Cons. at 25% (P.R.P.)	16.50 l/h

GENERAL ALTERNATOR DATA

Alternator brand	STAMFORD
Alternator model	UCI274H
P.R.P. Power	237.5 kVA
L.T.P. Power	256.3 kVA
Winding	Three phases Parallel Star
Terminals Number	12.00 nr.
IP Protection	23
Electronic regulator	AS440
Precision	± 1.00 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand	PERKINS
Engine model	1206A-E70TTAG3
Cylinders	6
R.P.M.	1800
Cubic capacity	7.01
Air intake	Turbo
Standard voltage	12 Vdc
Sae	-
BMEP	2064 kPa
Cooling	Water
Flywheel P.R.P. Power	202 kW
Flywheel Stand-by Power	224.6 kW
Electronic regulator	Standard
Precision class	G2
Oil quantity	16.00
Engine Antifreeze capacity	13.70
Radiator type	Tropicalized
Heat from radiator	182.70 kW
Heat from exhaust	246.30 kW
Heat from radiation	0.00 kW
Exhaust temperature	505 °C
Cooling air flow	337.20 m³/min
Combustion air flow	14.00 m³/min
Exhaust gas flow	31.20 m³/min
EU Stage	Not available

CONTROL PANELS

DSE4520



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.