

GENSET MODEL

Model **C 1000**

Mechanical version Open version with compact base frame and modular fuel tanks.

Fuel Tank Capacity l. 0

RATED TECHNICAL DATA

Prime Power (PRP) 1000.00 kVA

Prime Power (PRP) 800.00 kW

Emergency power (E.P.) 1100.00 kVA

Emergency power (E.P.) 880.00 kW

Rated Power Factor (cosφ) 0.8

Windings Three phases Series Star

Rated three-phase concatenated voltage 400 V

Rated phase-neutral voltage 230 V

Rated frequency 50 Hz

Fuel type Diesel

DIMENSIONS AND NOISE

Length 5000 mm

Width 2200 mm

Height 2400 mm

Weight 9240 kg

Sound pressure 7 m. - dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (E.P.) 228.00 l/h

Fuel Cons. at 100% (P.R.P.) 209.00 l/h

Fuel Cons. at 75% (P.R.P.) 161.00 l/h

Fuel Cons. at 50% (P.R.P.) 113.00 l/h

Fuel Cons. at 25% (P.R.P.) 65.00 l/h

GENERAL ALTERNATOR DATA

Alternator brand STAMFORD

Alternator model HCI6J

P.R.P. Power 1030.0 kVA

E.P. Power 1110.0 kVA

Winding Three phases Series Star

Terminals Number 12.00 nr.

IP Protection 23

Electronic regulator MX322

Precision ± 0.50 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand CUMMINS

Engine model KTA38-G5

Cylinders 12

R.P.M. 1500

Cubic capacity 37.80

Air intake Turbo

Standard voltage 24 Vdc

Sae -

BMEP 1868 kPa

Cooling Water

Flywheel P.R.P. Power 857 kW

Flywheel E.P. Power 947 kW

Electronic regulator Standard

Precision class G3

Oil quantity 135.00

Engine Antifreeze capacity 124.00

Radiator type Tropicalized

Heat from radiator 594.00 kW

Heat from exhaust 590.00 kW

Heat from radiation 137.00 kW

Exhaust temperature 513 °C

Cooling air flow 1134.00 m³/min

Combustion air flow 72.80 m³/min

Exhaust gas flow 198.40 m³/min

EU Stage Not available

CONTROL PANELS

AMF25



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement. **E.P. - Emergency power:** This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.

