

GENSET MODEL

Model	V 415
Mechanical version	Open version with compact base frame and high capacity integrated fuel tank without collection basin.
Fuel Tank Capacity l.	900

RATED TECHNICAL DATA

Prime Power (PRP)	412.00 kVA
Prime Power (PRP)	329.60 kW
Limited Power (LTP)	452.00 kVA
Limited Power (LTP)	361.60 kW
Rated Power Factor (cosφ)	0.8
Windings	Three phases Series Star
Rated three-phase concatenated voltage	400 V
Rated phase-neutral voltage	230 V
Rated frequency	50 Hz
Fuel type	Diesel

DIMENSIONS AND NOISE


Length	3140 mm
Width	1280 mm
Height	2020 mm
Weight	3310 kg
Sound pressure 7 m.	- dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (L.T.P.)	90.30 l/h
Fuel Cons. at 100% (P.R.P.)	81.80 l/h
Fuel Cons. at 75% (P.R.P.)	62.30 l/h
Fuel Cons. at 50% (P.R.P.)	42.10 l/h
Fuel Cons. at 25% (P.R.P.)	23.10 l/h

GENERAL ALTERNATOR DATA

Alternator brand	STAMFORD
Alternator model	S4L1D-F
P.R.P. Power	415.0 kVA
L.T.P. Power	465.0 kVA
Winding	Three phases Series Star
Terminals Number	12.00 nr.
IP Protection	23
Electronic regulator	AS440
Precision	± 1.00 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand	VOLVO-PENTA
Engine model	TAD1344GE
Cylinders	6
R.P.M.	1500
Cubic capacity	12.78
Air intake	Turbo
Standard voltage	24 Vdc
Sae	-
BMEP	2300 kPa
Cooling	Water
Flywheel P.R.P. Power	354 kW
Flywheel Stand-by Power	389 kW
Electronic regulator	Standard
Precision class	G3
Oil quantity	36.00
Engine Antifreeze capacity	0.00
Radiator type	Tropicalized
Heat from radiator	143.00 kW
Heat from exhaust	243.00 kW
Heat from radiation	13.00 kW
Exhaust temperature	440 °C
Cooling air flow	0.00 m³/min
Combustion air flow	27.00 m³/min
Exhaust gas flow	0.00 m³/min
EU Stage	STAGE 2

CONTROL PANELS

AMF25



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.