

GENSET MODEL

Model **D 21 ES**

Mechanical version Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, integrated fuel tank without collection basin.

Fuel Tank Capacity l. 90

RATED TECHNICAL DATA

Prime Power (PRP) 20.00 kVA

Prime Power (PRP) 16.00 kW

Emergency power (E.P.) 21.30 kVA

Emergency power (E.P.) 17.04 kW

Rated Power Factor (cosφ) 0.8

Windings Three phases Series Star

Rated three-phase concatenated voltage 400 V

Rated phase-neutral voltage 230 V

Rated frequency 50 Hz

Fuel type Diesel

DIMENSIONS AND NOISE

Length 2100 mm

Width 930 mm

Height 1280 mm

Weight 730 kg

Sound pressure 7 m. 69.0 dBA

FUEL CONSUMPTION

Fuel Cons. at 100% (E.P.) 5.60 l/h

Fuel Cons. at 100% (P.R.P.) 5.30 l/h

Fuel Cons. at 75% (P.R.P.) 4.00 l/h

Fuel Cons. at 50% (P.R.P.) 3.10 l/h

Fuel Cons. at 25% (P.R.P.) 2.50 l/h

GENERAL ALTERNATOR DATA

Alternator brand STAMFORD

Alternator model SOL2-G

P.R.P. Power 20.0 kVA

E.P. Power 22.0 kVA

Winding Three phases Series Star

Terminals Number 12.00 nr.

IP Protection 23

Electronic regulator VITA01

Precision ± 0.50 %



For illustrative purposes only

GENERAL ENGINE DATA

Engine brand DEUTZ

Engine model F3M2011

Cylinders 3

R.P.M. 1500

Cubic capacity 2.33

Air intake Aspirated

Standard voltage 12 Vdc

Sae -

BMEP 690 kPa

Cooling Oil

Flywheel P.R.P. Power 19.4 kW

Flywheel E.P. Power 20.4 kW

Electronic regulator On request

Precision class G2

Oil quantity 8.50

Engine Antifreeze capacity 0.00

Radiator type Tropicalized

Heat from radiator 11.30 kW

Heat from exhaust 18.10 kW

Heat from radiation 0.00 kW

Exhaust temperature 540 °C

Cooling air flow 30.00 m³/min

Combustion air flow 0.00 m³/min

Exhaust gas flow 4.16 m³/min

EU Stage STAGE 2

CONTROL PANELS

DSE4520



STANDARD REFERENCE CONDITIONS

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment, any optional and additional equipment/accessories can modify weight, dimensions, performance. **P.R.P. Prime Power-Continuous power at variable load.** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer. **L.T.P. Limited-time running power-Limited power.** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted. The data contained in this document is nominal and refers to the standard equipped model and is not binding. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement. **E.P. - Emergency power:** This is the maximum power that a generating set can deliver for a limited number of hours per year while complying with the maintenance frequency stipulated under the environmental conditions set by the Manufacturer. The number of hours per year is determined by the engine manufacturer. The average power output over time must be lower than the percentages set by the engine manufacturer. Overloading is not allowed.